
Slide 1 - Design-Bid-Build vs. Design-Build Process




# Slide notes

This section will compare a design bid build project to a design build project. We will also illustrate how each of these methods impacts the decision process and who is responsible for initiating unforeseen changes during the construction process.

Notes		

# Slide 2 - Methodology




# Slide notes

There are two different methods that SHA currently utilizes for designing and building construction projects. The Design-Bid-Build method is the traditional process utilized in horizontal construction. This is the lowest bidder method. The Design-Build process is a newer process utilized on select projects based on multiple factors from scope of work, to complexity, to cost. Design-Build projects can have many benefits as we will see in this presentation.

Notes				
	·	·	·	·
		_		_

# Slide 3 - Design-Bid-Build (DBB)



### Slide notes


Looking in detail at the various steps involved in the process of building a roadway, we can see the amount of time involved. With a Design-Bid-Build project, planning, environmental studies and NEPA compliance can take several years. SHA will then design the plans and put together an invitation for bids. Contractors will bid on the project and generally the lowest bidder will be awarded the work. Construction can then begin.

This entire process can take seven to 13 years.

Note that SHA accepts full responsibility for design errors and change orders since SHA designed the plans.

N	-1
N	<b>NTAC</b>

# Slide 4 - Design-Build (D/B)



### Slide notes


For a Design-Build project of the same type, the planning, environmental studies and NEPA compliance will still take about the same amount of time. The difference shows in the design phase. A Design-Build project may be from zero to 30 percent designed by SHA.

The Administration will then create an invitation for proposals and contractors will compete for the contract through a best value review process. Once the contract is awarded to the Design Builder, design and construction can begin concurrently.

The same project built with this method may only take five to seven years from concept to completion.

Notes			

# Slide 5 - Design-Build (D/B)




# Slide notes

There are many benefits with the Design-Build process such as, improved design timeframes along with phased design and construction leading to a finished project in a much shorter timeframe. The Design Builder can bring new innovations into the project as the contractor is a part of the DB team.

A key difference to note is that the Design Builder is responsible for design error and changes as they are the team that developed the plan.

Notes		

# Slide 6 - Design-Build (D/B)



# Slide notes

Erosion and Sediment Control Plan approval is given at each phase of the design submittal. SHA is identified as the permit owner and retains control over erosion and sediment control.

Notes			

Slide 7 - Personnel Responsibilities for ESC

Personnel Responsibilities for ESC					
Personnel	Design-Bid-Build (DBB)	Design-Build (DB)			
SHA Inspector's Role	When design issue identified, Contact SHA Project Engineer	Same			
Contractor's E&S Control Manager (ESCM) Role	Works with SHA Inspector and Construction Project Engineer	Works with SHA Inspector, Construction Project Engineer, their own design engineers			
Regional Environmental Coordinator	Conduct bi-weekly QA reviews	Same			
Environmental Monitor's Role	May not be assigned unless a sensitive resource is identified on the project	Most likely to have one; Works with SHA Inspector, ESCM, Construction Project Engineer			

# Slide notes

When looking at the responsibilities of the different team members, we can see that there are only a few key differences. The contractor erosion and sediment control manager will have the added responsibility of working with the DB team on any issues that may arise in the field.

An environmental monitor may be assigned to the Design-Build project as a condition of the permits. The role of the environmental monitor will be further discussed in the organization section of the training.

Notes			

# Slide 8 - E&S Control & Design-Build



# Slide notes

The work on a Design-Build contract is bid as a lump sum item and therefore all work associated with the installation and maintenance of E & S Controls are inclusive in the price. Some contracts may include a severe weather specification for additional compensation when a severe weather event occurs during the construction phase of the project.'

Notes			

# Slide 9 - E&S Control & Design-Build

# Contractor is responsible for implementing and maintaining the approved E&S Plan with the requirement that sediment is contained on site and does not discharge off-site. Additional controls may be required to contain sediment beyond the approved E&S Control Plans. If necessary, implementation of additional controls are to follow the specifications and appropriate guidelines. Each Invitation for Bids (IFB) should be read carefully before bidding since there could be variations in the terms of the DB contracts.

### Slide notes

The contractor must follow the approved E & S plan on a Design-Build site. If additional controls are necessary in order to meet the permit obligations, additional payment is not considered as all work is bid under a lump sum item. The contract documents should be read carefully and understood by all team members.

Notes		

# Slide 10 - End



# Slide notes

This concludes the Design-Build portion of the training. Please select the next module to continue the training

Notes			