

Asphalt Technology Division

Chandra Akisetty, Division Chief443-572-5051Rebeccah Smith, Assistant Division Chief – Field Operations443-572-5112Zhaoxing Xie, Assistant Division Chief – Laboratory443-572-5113



Asphalt Additives

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing	Page 1 of 1			
Source Level Materials		Specification	Comments	
Anti-Strip		904.04.08		
WMA: Binder Additive		904.04.08		
WMA: Mixture Additive		904.04.08		

Plant or Product Qualification

Evaluation of Production Facility for ATD Materials

Production facility data maintained to track the material supply chain and provide a basis for qualified products.

Address and low level information is maintained to provide data of facilities that produce this category's material types. Facilities that produce materials in this category will be given a status of "Product Qualification Required".

1 per 1 Prior to Usage on Project

Evaluation of Material Product for ATD Materials

Qualification of Material Product for use on State Projects

New products for this category will be evaluated through the MPEL system. Navigate to "http://www.roads.maryland.gov/index.aspx?PageID=600" for the current qualified list and detailed procedures. Navigate to "http://apps.roads.maryland.gov/MPEL/" for new submissions.

1 per 1 Prior to Usage on Project

Facility Qualification

Product Qualification

Asphalt Mixtures

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 4

Source Level Materials	Specification	Comments	
12.5mm DHMA	904.04.02		
19mm DHMA	904.04.02		
25mm DHMA	904.04.02		
37.5mm DHMA	904.04.02		
4.75mm DHMA	904.04.02		
9.5mm DHMA	904.04.02		
12.5mm GSMA	904.05.02		
19mm GSMA	904.05.02		
9.5mm GSMA	904.05.02		
12.5mm OGFC	927		
9.5mm OGFC	927		
12.5mm UTBWC	Special Provisions		
9.5mm UTBWC	Special Provisions		
4.75mm HPTO	Special Provisions		
Plant or Product Qualification			

Plant or Product Qualification

Evaluation of Production Facility for ATD Materials

Facility Qualification

Production facility to be certified to produce material for State projects.

The material producer shall be reviewed by the Asphalt Technology Division prior to being named as a Source of Supply. Each year Asphalt Mix production plants that wish to produce for State projects will go through a start-up inspection performed by OMT staff.

1 per 12	Months	
Evaluation of Material Product for ATD Materi	als	Product Qualification

Review and Qualification of Asphalt Mixture Material Product.

Individual asphalt mixtures shall be approved for state use prior to being used on any project.

1 per	1	Prior to Source Request	
SHA Acceptance Facility Visit for Asp	bhalt I	Mix Production	Product QC/QA

OMT personnel shall process the Asphalt Mix Plant QA checklist to ensure that the Quality Control plan is being followed and operations are performed correctly.

Production Quality Assurance

1	per	10	Production Day
1	per	6000	Ton

Asphalt Mixtures

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 2 of 4

SHA Acceptance of Binder Component

Product QC/QA

Asphalt Technology representative to witness and take possession of material sample. Samples to be taken from the plant sampling device. 1 Quart in a Friction Top Can **Project Completion** 1 per 1 1 per 10 Production Day per 6000 Ton Source Approval Source of Supply Submittal Source Submission A name and address of the material sources of supply shall be sent to MMD for review. The producer is the organization that creates the material, the supplier is the one that delivers it to the project. Material Producer and Product must be on qualified lists and associated correctly prior to source approval. If either cannot be accomplished the source will be rejected. Source of Supply Processing 1 per 1 Prior to Usage on Project **Material Production** Production Notification Notification of Production for ATD materials Producer to notify the Asphalt Technology Division 1 day prior to production. Producer to notify ATD anticipated quantity of Asphalt Mix production and actual quantity of previous day's production. 1 per 1 Placement Day **Project Construction Core Sampling for Asphalt Mix Density Analysis** Material Sampling and Testing Steps will be taken to ensure the density of the placed material is of an adequate density. If the density does not meet specifications a pay adjustment may take place, or the material may be removed and replaced. Cores will be taken after compaction and prior to opening for traffic. Project Engineer shall verify that the contractor takes QC and QA Density Cores at random locations in the pavement. (1 Sample = 5 Cores Min. See Material QA Manual for more information) One sample for QA and will be delivered to OMT for analysis. One sample for QC and will be analyzed by the producer with results sent to OMT. 5 cores per sample (Minimum). If daily quantity is greater than 2500 Ton additional cores are required at a rate of 1 core per sample per 500 Ton (or fraction thereof). Cores are typically 6" diameter, however 4" diameter cores allowed on 19mm or smaller mixtures. 1 Sample = 5 - 6" Dia. Cores (min) Production Day 2 per 1 Material Sampling and Testing **Density Gauge testing for Patches or Small Quantities**

Task is only applicable if the asphalt mixture is placed in patches or small daily quantities (<200 tons). The results are for tracking purposes only and will not be incorporated into a pay factor.

Asphalt Mixtures

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 3 of 4


Patch density measured at random locations with an asphalt density gauge, recorded on a Form 73-1P and submitted to OMT. See specification 505.03.14 for additional details.

2 Readings per test

1 per 1 Lift of each Patch

Box Sampling for Asphalt Mixture

Samples of the asphalt mixture will be taken at random intervals behind the paver and be analyzed at the respective laboratories. Results will be utilized in determining a mixture pay factor. Producer's data is only included if the sample was taken behind the paver. If multiple mix formulations are utilized the frequencies indicated are for each mixture that is placed.



When daily placed quantity of asphalt mixture is low (<200 ton) samples of the asphalt mixture will be taken less frequently. These will occur at random intervals behind the paver and be analyzed at the respective laboratories. Results will be utilized in determining a mixture pay factor and statistical analysis, the producer's data is only included if the sample was taken behind the paver. If multiple mix formulations are utilized the frequencies indicated are for each mixture that is placed.

Project Engineer shall verify that the contractor takes QC and QA Box Samples at random intervals at least once per mix for every 1000 tons or once per mix weekly, whichever yields the greater frequency. See 505.03.12 for additional details. One sample for QA and will be delivered to OMT for analysis. One sample for QC and will be analyzed by the producer with the results sent to OMT. 1 Sample = 1-50 LB Box (2-50 LB for 25.0mm Mix, 2-50 LB for 37.5mm Mix) 2 per 5 Placement Day 2 per 1000 Ton

Results from the Producer's QC data and OMT's QA data will be statistically analyzed and a daily density pay factor will be produced.

Density QA and QC results are to be processed by the Asphalt Technology Division to develop a recommended "Density Pay Factor".

1 per	1	Sample Set	
Asphalt Mix Pay Factor Analysis			Sample Analysis

The Producer's QC data and OMT's QA data will be statistically analyzed and a mix pay factor will be generated when the appropriate number of samples have been received. QC data will only be incorporated into the Pay Factor Analysis if the sample was taken from behind the paver.

Mixture QA and QC results are to be processed by the Asphalt Technology Division to develop a recommended "Mixture Pay Factor".

1	per	1	Project Completion
1	per	6000	Ton

Material Sampling and Testing

Asphalt Mixtures

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 4 of 4

Evaluation of Pavement Surface Profile

This task is applicable to the final pavement's ride quality and is performed when Section 535 is included in the contract's special provisions and indicates that it is required.

Surface profiling will be completed as indicated in Section 535 of the Special Provisions.

See the State Highway Web Site for "SHA Ride Specification" (http://www.roads.maryland.gov/Index.aspx?PageId=32) for additional information.

1 per 1 Item Completion

Project Wide Testing

Asphalt Release

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 1

Source Level Materials	Specification	Comments
Asphalt Release Agents	915.02(f)	
Plant or Product Qualification		

Evaluation of Production Facility for ATD Materials

Production facility data maintained to provide a basis for qualified products.

Address and low level information is maintained to provide data of facilities that produce this category's material types. Facilities that produce materials in this category will be given a status of "Product Qualification Required".

1 per 1 Prior to Usage on Project

Evaluation of Material Product for ATD Materials

Product Qualification

Facility Qualification

Qualification of Material Product.

New products for this category will be evaluated through the MPEL system. Navigate to "http://www.roads.maryland.gov/index.aspx?PageID=600" for the current qualified list and detailed procedures. Navigate to "http://apps.roads.maryland.gov/MPEL/" for new submissions.

1 per 1 Prior to Usage on Project

Emulsified Asphalts, Other

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 1

S
on

Plant or Product Qualification

Evaluation of Production Facility	/ for ATD Materials

Production facility to be certified to produce material for State projects.

Each year Emulsified Asphalt production plants that wish to produce for State projects will submit a QC plan to be reviewed by the Asphalt Technology Division for conformance to AASHTO R 77.

1 per	12	Months	
Evaluation of Material Product for A	TD Mat	erials	Product Qualification

Qualification of Material Product for use on State Projects.

New products for this category will be evaluated through the MPEL system. Navigate to "http://www.roads.maryland.gov/index.aspx?PageID=600" for the current qualified list and detailed procedures. Navigate to "http://apps.roads.maryland.gov/MPEL/" for new submissions.

1 per 1 Prior to Usage on Project

Source Approval

Source Submission

A name and address of the material sources of supply shall be sent to MMD for review. The producer is the organization that creates the material, the supplier is the one that delivers it to the project.

Material Producers must be on a qualified list prior to source approval. If the Contractor sources a producer that is not on the qualified list, he will be advised that the source approval is contingent on a qualification process, the procedures, and duration. If he still wishes to use this product, he will need to advise the material producer / vendor to contact the New Products team for procedures.

Source of Supply Processing

1 per 1

Prior to Usage on Project

Project Construction

ATD Material Verification Material Verification

The Project Engineer shall verify that the material is from the correct source and supervise sampling of materials during delivery to the project site. The Project Engineer shall witness the sampling, collect certifications and have them delivered to OMT for testing.

Project Engineer to collect certifications (TC 1.03 w/ test data), FORM 88, and material samples. Submit items to OMT for testing and clearance.

Material Certification corresponds to a "Certificate of Analysis". This is not to be confused with a Bill of Lading / ShippingTicket.Sample containers must conform to the requirements outlined in AASHTO R 66.

1 Gallon in a Widemouth Plastic Jar

1 per 1 Item Completion

Facility Qualification

Source of Supply Submittal

Emulsified Asphalts, Tack Coat

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 2

Source Level Materials	Specification	Comments	
CQS-1HP	904.03		
CRS-1	904.03		
CRS-1h	904.03		
CRS-1P	904.03		
CRS-2L	904.03		
CRS-2P	904.03		
CSS-1h	904.03		
Non-Tracking Tack Coat	904.03		
SS-1h (Tack Coat)	904.03		
Plant or Product Qualification			

Evaluation of Production Facility for ATD Materials

Production facility to be certified to produce material for State projects.

Each year Emulsified Asphalt production plants that wish to produce for State projects will submit a QC plan to be reviewed by the Asphalt Technology Division for conformance to AASHTO PP 71.

1 p	er 12	
-----	-------	--

Evaluation of Material Product for ATD Materials

Emulsified asphalt products that are approved for use on state projects shall appear on the Qualified Products list that is managed by OMT. To be placed on this list the refinery shall submit emulsion samples and certification to OMT for testing and review.

Months

Qualification of Material Product for use on State Projects

New products for this category will be evaluated through the MPEL system. Navigate to "http://www.roads.maryland.gov/index.aspx?PageID=600" for the current qualified list and detailed procedures. Navigate to "http://apps.roads.maryland.gov/MPEL/" for new submissions.

1 per 1 Prior to Source Request

Source Approval

Source Submission

A name and address of the material sources of supply shall be sent to MMD for review. The producer is the organization that creates the material, the supplier is the one that delivers it to the project.

Material Producers must be on a qualified list prior to source approval. If the Contractor sources a producer that is not on the qualified list, he will be advised that the source approval is contingent on a qualification process, the procedures, and duration. If he still wishes to use this product, he will need to advise the material producer / vendor to contact the New Products team for procedures.

Source of Supply Processing

1 per 1

Prior to Usage on Project

Project Construction

Facility Qualification

Product Qualification

Source of Supply Submittal

Emulsified Asphalts, Tack Coat

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 2 of 2

ATD Material Verification

Material Verification

The Project Engineer shall verify that the material is from the correct source and supervise sampling of materials during delivery to the project site. The Project Engineer shall witness the sampling, collect certifications and have them delivered to OMT for testing.

Project Engineer to collect certifications (TC 1.03 w/ test data), FORM 88, and material samples. Submit items to OMT for testing and clearance.

Material Certification corresponds to a "Certificate of Analysis". This is not to be confused with a Bill of Lading / Shipping Ticket. Sample containers must conform to the requirements outlined in AASHTO R 66.

1 Gallon in a Widemouth Plastic Jar

1 per 1 Item Completion

Pavement Repair Materials

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing	Page 1 of 1		
Source Level Materials	Specific	cation	Comments
Asphaltic Joint Sealant and Crack Filler	911.01	L	
Cold Patch Material (CPM)	924		
Plant or Product Qualification			
Review of Producer (QPL)			Facility Qualification

Production facility data maintained to provide basis for gualified products.

Address and low level information is maintained to provide data of facilities that produce this category's material types. Facilities that produce materials in this category will be given a status of "Product Qualification Required".

	1	per	1	Prior to Source Request	
eview of Product (QPL)					Product Qualification

Qualification of Material Product for use on State Projects.

New products for this category will be evaluated through the MPEL system. Navigate to "http://www.roads.maryland.gov/index.aspx?PageID=600" for the current qualified list and detailed procedures. Navigate to "http://apps.roads.maryland.gov/MPEL/" for new submissions.

Source Approval

Rev

Source Submission

A name and address of the material sources of supply shall be sent to MMD for review. The producer is the organization that creates the material, the supplier is the one that delivers it to the project.

Source of Supply Processing

1 per 1

Prior to Usage on Project

Project Construction

ATD Material Verification	Material Verification

The Project Engineer shall verify that the material is from the correct source and supervise sampling of materials during delivery to the project site. The Project Engineer shall witness the sampling, collect certifications and have them delivered to OMT for testing.

Project Engineer to collect certifications (TC 1.03 w/o test data) and submit certs to OMT for clearance.

> 1 per 1 **Delivery to Project**

Source of Supply Submittal

Performance Graded Asphalt Binder

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 1

A (585-22) 904.02 B (585-28) 904.02 C (645-22) 904.02 D (645-28) 904.02 E (64H-22) 904.02	Source Level Materials	Specification	Comments
C (64S-22) 904.02 D (64S-28) 904.02	A (58S-22)	904.02	
D (64S-28) 904.02	B (58S-28)	904.02	
	C (64S-22)	904.02	
E (64H-22) 904.02	D (64S-28)	904.02	
	E (64H-22)	904.02	
F (64E-22) 904.02	F (64E-22)	904.02	
G (76E-28) 904.02	G (76E-28)	904.02	

Plant or Product Qualification

Evaluation of Production Facility for ATD Materials

Facility Qualification

The binder supplier shall submit a Quality Control Plan per AASHTO R26.

Qualification of Binder Supplier for use on State projects

Address and low level information is stored to track material supply chain. The specific materials supplied, and the qualification status is maintained by the Asphalt Technology Division. New producers or recertification requests will be submitted through the MPEL system (http://apps.roads.maryland.gov/MPEL).

1 per 1 Prior to Usage on Project

Evaluation of Material Product for ATD Materials Product Qualification

Product data and certifications of all compliant lots/tanks will be stored to serve as a baseline for future QC/QA samples.

Start-up Samples: Product, Lot/Tank identifiers, and binder analysis are determined by the binder supplier and shall be submitted to the Asphalt Technology Division via email prior to delivery to the asphalt mix producer. A material certification (TC 1.03 w/ test data) shall accompany the binder shipment to the production plant and will be retained by the plant until ATD arrives to collect QA samples. A copy of the certification will be retained by the plant until ATD arrives to collect QA samples.

Source Change: Asphalt Technology Division shall verify the material and data complies to specification when a source change is required during state production

Qualification of Material Product.

Done for each new batch of binder product produced by the refinery.

1 per 1 Batch, Lot or Heat

Recycled Materials for HMA Mixtures

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 1

Source Level Materials	Specification	Comments	
Bag House Fines			
Millings, General	904.04.02		
RAP (Reclaimed Asphalt Pavement)	904.04.02		
RAS (Reclaimed Asphalt Shingles)			
Plant or Product Qualification			

Joint Qualification with Asphalt Mix production facility.

Qualification of producers of Recycled Materials for asphalt mixtures is aggregated into the Qualification of HMA Producers.

1 per 1 Prior to Source Request	
Evaluation of Material Product for ATD Materials	Product Qualification
RAP and RAS Stock Piles will be identified and recorded prior to usage within an asphalt mixture.	
Qualification of Material Product.	

1 per 1 Prior to Source Request

Source Approval

Sourc	e Submissi	ion				Source	of Supply	Submittal

A name and address of the material sources of supply shall be sent to MMD for review. The producer is the organization that creates the material, the supplier is the one that delivers it to the project.

This material category is only sourced when millings are being used as a fill material. For example, "Millings for Shoulder Edge Drop-off". When this occurs the pre-qualification requirements of the product are relaxed. Pre-Qualification of this material category is more strict when it is used as a component of asphalt mixtures.

Source of Supply Processing

1 per 1

Prior to Usage on Project

Project Construction

ATD Material Verification Material Verification

The Project Engineer shall verify that the material is from the correct source and supervise sampling of materials during delivery to the project site. The Project Engineer shall witness the sampling, collect certifications and have them delivered to OMT for testing.

Project Engineer to visually inspect placed material and submit Form 14 to OMT for clearance.

Used when millings are specifically used on the project. For example, millings for shoulder edge drop-off.

1 per 1 Item Completion

Facility Qualification

Surface Treatments

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 1 of 2

Source Level Materials	Specification	Comments	
Slurry Seal / Micro-surfacing	923		
Type I - Slurry Seal	923		
Type II - Slurry Seal	923		
Type III - Slurry Seal	923		

Plant or Product Qualification

Facility Qualification

Product Qualification

Source of Supply Submittal

Production Notification

Production facility data maintained to provide a basis for qualified products.

Address and low level information is maintained to provide data of facilities that produce this category's material types. Facilities that produce materials in this category will be given a status of "Product Qualification Required".

> 1 per 1

Prior to Source Request

Evaluation of Material Product for ATD Materials

Slurry seal products must be qualified by the Asphalt Technology Division prior to project sourcing. See 923.05 for further details.

Review and Qualification of Material Mixture for use on State Projects.

Individual asphalt mixtures shall be approved for state use prior to being used on any State project by the Asphalt Technology Division.

1 per 1

Prior to Source Request

Source Approval

Source Submission

A name and address of the material sources of supply shall be sent to MMD for review. The producer is the organization that creates the material, the supplier is the one that delivers it to the project.

A material product must be qualified and associated to the source request prior to approving the source. Correct association is implied by selecting the product from the product association dropdown list and having a mix design sheet attached. If this cannot be accomplished the submission will be rejected.

Source of Supply Processing

1 per 1

Prior to Usage on Project

Material Production

Notification of Production for ATD materials

Producer to notify the Asphalt Technology Division one week prior to material placement.

1 per 1

Placement Day

Project Construction

Surface Treatments

Asphalt Technology Division

QA / Frequency Guide, Source Level Material Listing Page 2 of 2

ATD Material Verification

Material Verification

Material Sampling and Testing

This product may be required to be Buy America compliant under the Infrastructure Investment and Jobs Act (IIJA) / Bipartisan Infrastructure Law (BIL). A statement of compliance with Buy America from the manufacturer/producer must be included with every delivery to the project and must identify where the material was manufactured/produced.

The Project Engineer shall verify that the material is from the correct source and supervise sampling of materials during delivery to the project site. The Project Engineer shall witness the sampling, collect certifications and have them delivered to OMT for testing.

Project Engineer to collect material certifications (TC 1.03 w/o test results) and submit to materials management for clearance.

See MD Specification 507.03 for further details on specification requirements.

1 per 1

Delivery to Project

Sampling and Testing of ATD materials

Project Engineer to sample emulsion and mixture. Sample to be delivered to OMT for verification.

Sample containers must conform to the requirements outlined in AASHTO R 66.

1 Gallon of Mixture and 1 Gallon of Emulsion in a Widemouth Plastic Jar

1 per 1 Production Day